



THE END.™

Wasp & Hornet Killer

FEATURES

- Instant Knockdown
- Sprays up to 20 feet
- Dielectric breakdown voltage of 40,700 volts
- Kills wasps, hornets, yellow jackets, and bees
- Kills nest and insects with residual action

APPLICATIONS

- Attics
- Eaves
- Screens
- Window Frames
- Crevices
- Doors
- Patios
- Cracks
- Holes



PROPERTIES

Appearance / Physical State	Liquid/Aerosol
Odor	Nearly Odorless
Melting / Freezing Point	Undetermined
Boiling Point / Range	221°C (430°F)
Vapor Pressure	80 - 100 psig @ 21°C (70°F)
Partition Coefficient	Not determined
Flammability	Not applicable
Propellant	Carbon Dioxide
VOC Content	0%
Color	Colorless
Flash Point	82°C (180°F)
Density	Not determined
pH Value	Not applicable
Vapor density	> 1 (Air=1)
Auto-Ignition Temperature	Not determined
Viscosity	Not determined
Density	0.779 - 0.799 g/cm (6.501 - 6.668 lbs/gal) @ 20°C (68°F)

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
18320	12 oz / 340 g	aerosol	12	13 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved



THE END.™

Wasp & Hornet Killer

DIRECTIONS

FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. For best results, spray in early morning or late evening when insect activity is minimal. Stand a safe distance from nest and not directly underneath. Hold can upright and point spray opening toward nest with wind at your back. Spray until nest is thoroughly saturated to kill the entire nest population. Residual action will kill wasps and hornets returning to the nest. Wait at least 24 hours before removing the nest. To kill wasps, hornets, yellow jackets and bees under eaves, screens, window frames, doors, patios, cracks, holes or crevices wherever insects are noticed, spray about 1 - 2 seconds or until surfaces are moist. To prevent entrance of insects into the house, spray around points where insects enter such as outside plumbing, faucets, etc., and cracks or crevices in foundation as well as along sills and ledges. Do not use in commercial food/feed handling establishments, restaurants or other sites where food/feed is commercially prepared or processed. Not for use in Federally inspected meat and poultry plants. Do not apply to pets or contaminate feed, foodstuffs, dishes or utensils. Avoid spraying vegetation directly. Restrictions: Do not allow adults, children, or pets to enter the treated area until sprays have dried. Do not apply this product in a way that will contact adults, children, or pets, either directly or through drift. Remove pets, birds, and cover fish aquariums before spraying. Do not make application during rain. Do not apply when food is present. Remove or cover exposed food and drinking water before application. Remove or cover dishes, utensils, food processing equipment, and food preparation surfaces, or wash them before use. Do not water the treated area to the point of run-off. Not for broadcast in indoor residential surfaces. All outdoor application must be limited to spot or crack-and-crevice treatments only. Other than applications to building foundations, all outdoor applications to impervious surfaces such as sidewalks, driveways, patios, porches and structural surfaces (such as windows, doors, and eaves) are limited to spot and crack-and-crevice applications only. Do not use around or near floor drains or in drains or sewers.

HANDLING

PRECAUTIONS: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid prolonged or repeated contact with skin. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

STORAGE

Store locked up. Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

D003: Waste Reactive material

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved