

RUST SPOT'R

RUST REMOVER

ALL PURPOSE RUST REMOVER



RUST SPOT'R® RUST REMOVER RTU

Rust Spot'R™ is a safer alternative for users and the environment, especially when compared to more traditional products that contain hydrofluoric, hydrochloric, oxalic and phosphoric acids!

This clear formula has a light fragrance and attacks rust quickly and effectively.

Professional, ready-to-use formula makes tough rust and corrosion spot removal easy.

REMOVES:

- ⊙ Rust
- ⊙ Iron
- ⊙ Mineral deposits
- ⊙ Corrosion

USE IN:

- ⊙ Concrete
- ⊙ Laundry
- ⊙ Upholstery
- ⊙ Natural Stone
- ⊙ Tile
- ⊙ Carpet
- ⊙ Drapery

Use sparingly and in an inconspicuous test area first.

Be sure to take action as quickly as possible once staining occurs.

Once Rust Spot'R™ is allowed to react with the stain, rust residue will break free of the surface and can be extracted or wiped with a sponge and water.

Product Codes: RS-100 Case of 12 | RS-500 Case of 12 RS-640 Case of 4

SPOTTERS

DIRECTIONS

Before Cleaning:

Test on surface before using. Apply a small amount of product to an inconspicuous area. If surface mars, dulls, discolors, fades or fiber color transfers to a white cloth, do not use.

Do not use silk, satin, velvet, leather, suede, latex, painted or varnished wood surfaces. May dull some plastics.

APPLICATION

Carpet & Upholstery:

1. Apply Unbelievable® Rust Spot'R™ directly to stained area.
2. Use 3-in-1 spotting tool or brush to work into stained area.
3. Blot with an absorbent, clean, white, towel.
4. Repeat until stain is removed.

Laundry:

1. Apply Rust Spot'R™ as directed for carpet & upholstery steps 1 & 2.
2. Machine wash. If stain persists, repeat.

Tile:

1. Remove any wax finish with stripper, thoroughly rinse and dry stained area.
2. Apply Rust Spot'R™ to stain and allow up to one minute dwell time.
3. Repeat steps if necessary.

Concrete/Natural Stone:

1. Thoroughly degrease and rinse area. Blot dry.
2. Apply Rust Spot'R™ to stain, and allow no more than 30 seconds dwell time.

NOTE: Extended exposure may cause whitening of concrete and/or etching of natural stone.



Ph: 903.567.1341 | Toll Free: 800.825.2673 | Fax: 903.567.1346

P.O. Box 669, 401 Industrial | Canton, TX 75103

Coreproductsco.com | [G+](#) [in](#) [You Tube](#) [f](#)

NOT TO BE SOLD IN THE STATE OF CALIFORNIA