

LOOSE SCREW

LUBRICANT & PENETRANT WITH PTFE



DESCRIPTION

LOOSE SCREW is a non-flammable, 4-in-1 formula that penetrates, lubricates, displaces moisture and resists corrosion. Displaces water and moisture from electrical equipment such as contact points and automotive distributors, machinery parts, guns and equipment. Fortified with PTFE. Contains no ozone depleters. Conforms to Military Specifications MIL-C-23411 for corrosion prevention. Due to VOC regulations, not available for sale in California and Utah.

APPLICATIONS

This lubricant is great for use on motors, wire cable, rusted parts, ignition systems, machine parts, door hinges, locks, nuts and bolts and refrigeration equipment. Used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, airlines, air maintenance shops, industrial plants, oil rigs, hotels/motels and general industries.

FEATURES & BENEFITS

- Non-Flammable
- Displaces Moisture
- 4-in-1 Lubricating & Penetrating Oil
- Contains PTFE to Inhibit Rust & Corrosion

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 200 ppm
WETTING ABILITY: Saturates
STORAGE STABILITY: 1 Year
COLD STABILITY: 0°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: N/A
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.365
% VOC: 0%
pH: N/A
VISCOSITY: Thin
EVAPORATION RATE: Fast
BIODEGRADABILITY: No

LABEL INFORMATION

LOOSE SCREW LUBRICANT & PENETRANT WITH PTFE

LOOSE SCREW is a non-flammable, 4-in-1 formula that penetrates, lubricates, displaces moisture and resists corrosion. Displaces water and moisture from electrical equipment such as contact points and automotive distributors, machinery parts, guns and equipment. This lubricant is used by factories, truck lines, delivery services, transit systems, schools, machine shops, service stations, airlines, air maintenance shops and general industries. Fortified with PTFE. Contains no ozone depleters. Conforms to Military Specifications MIL-C-23411 for corrosion prevention.

DIRECTIONS: Keep actuator pointed towards dot on valve cup. Remove cap. Direct spray toward area to be treated and spray generously until all moisture is rinsed away. Spraying action will also leave a protective coating to repel moisture. Repeat as needed. Can also be used to loosen rusty nuts and bolts.

DANGER: Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause cancer. May cause drowsiness or dizziness. Suspected of causing genetic defects.


Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves, eye protection, and protective clothing. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

WARNING: This product contains a chemical known to the State of California to cause cancer.

CONTAINS (CAS#): Tetrachloroethylene (127-18-4), Petroleum Distillate (8052-41-3), Trichloroethylene (79-01-6), Mineral Oil (8042-47-5), Carbon Dioxide (124-38-9).

NOTE: This product, due to its chlorinated solvent content, is prohibited for sale and use in the State of California. Other areas may also prohibit its sale and use. Check local and state regulations.

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL	C



PACKAGING INFORMATION

12 – 20 oz. cans per case, 19 oz. net weight