

RUST RELEASE LUBRICANT

FOAMING PENETRATING & CUTTING OIL



DESCRIPTION

RUST RELEASE provides effective lubrication in a variety of metalworking applications. The anti-friction properties prolong tool life. For use on farm equipment, sports equipment, industrial equipment, marine and auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.

APPLICATIONS

Formulated to loosen rusted parts and lubricate cutting or machining carbon alloys, stainless steel, chrome steel, copper, aluminum, magnesium, and bronze. Lubricates door hinges, chains, hoists, pulleys, cranes, fork lifts, sprockets, gears, blocks & tackle, conveyors, construction machinery, industrial parts and locks. Areas of use include farms, oil rigs and refineries, bottling plants, dairies, paper mills, cotton gins, air conditioning, industrial plants, textile plants, lumber mills, cement plants and automotive/motorcycle/marine repair.

FEATURES & BENEFITS

- Reduces metal-to-metal noise
- Resists rust and corrosion even in extreme conditions
- Prolongs tool life

SPECIFICATIONS

FORM: Oil Based Aerosol	FLASH POINT: N/A
ODOR: Mild Petroleum	FLAME EXTENSION: 18" +
COLOR: Brown	SOLUBILITY IN WATER: 0%
DETERGENCY: None	SPECIFIC GRAVITY: 0.92
TOXICITY: 1000 ppm OSHA TLV	% VOLATILE BY VOLUME: 98%
WETTING ABILITY: Saturates	pH: N/A
STORAGE STABILITY: 1 Year +	PROPELLANT: Hydrocarbon
COLD STABILITY: 0°F	EVAPORATION RATE: Slow
PHOSPHATES: None	BIODEGRADABILITY: No

LABEL INFORMATION

RUST RELEASE FOAMING PENETRATING & CUTTING OIL

This product is designed to be used on farm equipment, sports equipment, industrial equipment, marine and auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.


DIRECTIONS: Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.

WARNING: This product can expose you to chemicals including Cumene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS #): Heavy Naphthenic Petroleum Distillate (64742-52-5), Propane/n-Butane (68476-86-8), Mineral Spirits (8052-41-3), Oxygenated Hydrocarbon (N/A).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 20 oz. cans per case, 16 oz. net weight