

Technical Data Report

EZ LUBE

FOOD GRADE WHITE GREASE



DESCRIPTION

EZ LUBE food grade white grease is a high purity complex white grease with superior heavy-duty metal-to-metal characteristics. Excellent for high load applications requiring a long grease life. Resists water and heat. Provides rust corrosion protection and superior lubrication to a wide variety of applications. Wide temperature range of -40°F to +550°F.

APPLICATIONS

FOR USE ON: Chains, winches, conveyors, gears, cables, hinges, pins, levers, rollers, ovens, dryers, threads, bearings, O-rings, linkages, pumps and valves. **FOR USE BY:** Bakeries, bottlers, breweries, canneries, dairies, egg processors, meat and poultry processors, pharmaceutical manufacturers and food processing and packaging plants.

FEATURES & BENEFITS

- Lubricates, reducing friction and wear
- Resists extreme pressure, corrosion & water washout
- White coloration for easy visual check
- High viscosity, clings to vertical surfaces
- Wide temperature range of -40° – 550°F
- Resists throw-off, excellent adhesion properties

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Petroleum
COLOR: Opaque White
DETERGENCY: None
TOXICITY: 500 ppm OSHA TLV
WETTING ABILITY: None
STORAGE STABILITY: 1 year +
COLD STABILITY: 32°F
PHOSPHATES: None

FLASH POINT: N/A
FLAME EXTENSION: 18" +
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.850
% VOLATILE BY VOLUME: 71%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

EZ LUBE FOOD GRADE WHITE GREASE

A multi-purpose, high purity food grade lubricant that provides long lasting grease protection. Cured lubricant withstands heat to 550°F. Temperatures above 400°F may require periodic reapplication.

FOR USE ON: Chains, Winches, Conveyors, Gears, Cables, Hinges, Pins, Levers, Rollers, Ovens, Dryers, Threads, Bearings, O-Rings, Linkages, Pumps and Valves.


FOR USE BY: Bakeries, Bottlers, Breweries, Canneries, Dairies, Egg Processors, Meat and Poultry Processors, Pharmaceutical Manufacturers and Food Processing and Packaging Plants.

DIRECTIONS: Shake well before using. Remove protective cap. Point opening in spray tip towards area to be sprayed. For hard to reach areas insert red extender tube in hole in tip. Apply a light coat by spraying in quick, short bursts. Work part to distribute product evenly over entire surface. Spray as necessary to insure full coverage.

DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye protection and protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Do not eat, drink or smoke while using this product. Dispose of contents and container in accordance with local, state, and national regulations.

CONTAINS (CAS#): Propane/n-Butane (68476-86-8), Hexane (110-54-3), Mineral Oil (8042-47-5).

HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL	B



Nonfood Compounds
 Program Listed H1
 148101

PACKAGING INFORMATION

12 – 16 oz. cans per case, 10 oz. net weight