

SURROUND

COLD PIPE INSULATION SPRAY



DESCRIPTION

SURROUND is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard to reach areas. Expanding spray conforms to irregularly shaped surfaces.

APPLICATIONS

For use on cold water pipes, valves and fittings, metal gutters, refrigeration lines, condenser lines and water tanks. Areas of use include air conditioning maintenance, aircraft maintenance, industrial operations, food plants, refrigeration trucks, cold storage lockers, shipping operations, kitchens and indoor ice rinks.

FEATURES & BENEFITS

- Durable finish may be painted or primed
- Repairs wrap around pipe insulation, prolonging life
- Water resistant coating prevents condensation and dripping

SPECIFICATIONS

FORM: Solvent Based Aerosol
ODOR: Chlorinated Solvent
COLOR: Clear
DETERGENCY: None
TOXICITY: 25 ppm OSHA TLV
WETTING ABILITY: None
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
PHOSPHATES: None
VOC CONTENT: 32%

FLASH POINT: N/A
FLAME EXTENSION: >18"
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 1.2
% VOLATILE BY VOLUME: 82%
pH: N/A
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Medium
BIODEGRADABILITY: None

LABEL INFORMATION

SURROUND COLD PIPE INSULATION SPRAY

Surround is a convenient, ready-to-use spray-on pipe insulator. Dries to a hard white coating which can be painted or primed when dry. Prevents sweating and dripping on cold water pipes, refrigeration lines, condensers, air conditioning lines, and other cold surfaces. Insulates water tanks, metal gutters, ducts and toilet tanks. Fan spray application provides an excellent method of repairing wrap around type insulation. Easy to apply to hard to reach areas. Expanding spray conforms to irregularly shaped surfaces.

DIRECTIONS: Remove dust and loose dirt from surface to be sprayed by wiping with a clean, dry cloth. Cover surfaces under area to be treated to avoid overspray. Shake can vigorously. Continue shaking for one minute and occasionally during use. For proper adhesion apply only to dry surfaces. Hold can 8-10 inches from surface. Apply with a sweeping motion using several thin coats. Allow each coat to dry thoroughly for several minutes before applying a new coat. If product runs, can is too close to surface.

WARNING: Flammable Aerosol. Contains gas under pressure; May explode if heated. May cause respiratory irritation, drowsiness or dizziness. Causes skin and serious eye irritation. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wear protective gloves and eye protection. Wash hands thoroughly after handling. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing dust, fumes or mist. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Dispose of contents and container in accordance with local, state, and national regulations.

WARNING: This product can expose you to chemicals including Dichloromethane, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CONTAINS (CAS #): Methylene chloride (75-09-2), Propane/n-Butane (68476-86-8), Acrylic Polymer (N/A), Hexadecenoic Acid (57-10-3), Octadecanoic Acid (57-11-4).

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	B



PACKAGING INFORMATION

12 - 20 oz. cans per case, 18 oz. net weight