

WONDER

ACOUSTICAL CEILING TILE RESTORER



DESCRIPTION

WONDER is a unique clay based restoring system for acoustic ceiling tiles. Permanently bonds to the surface being restored without compromising acoustical sound absorption or fire retardant value. Covers water stains, smoke and fire damage, graffiti, paint, ballpoint ink, permanent marker and rusting nail heads, avoiding the need for costly replacement. Leaves a clean, white coating that adds years to tile life. Also works as a nonbleeding primer/sealer for sign painters, a nongrain-raising primer for new wood, a base coat for wallpaper or vinyl wall coverings and as a base coat for galvanized metal.

APPLICATIONS

For use on acoustical ceiling tiles to restore appearance to like new, on new wood as a primer, on bare walls as a base coat for wallpaper or vinyl wallcovering and as a base coat for galvanized metal prior to painting. Areas of use include sign shops, fire and water damage restoration services, make-ready companies, office maintenance personnel, metal workers and woodworkers.

FEATURES & BENEFITS

- Covers a variety of stains and damage, eliminating immediate costly tile replacement
- Safely restores the appearance of tiles without compromising fire retardant value or sound absorption properties
- Economical—one can covers 12 to 15 (2'x4') tiles or 120 square feet

SPECIFICATIONS

| | |
|------------------------------------|------------------------------------|
| FORM: Solvent Based Aerosol | FLASH POINT: N/A |
| ODOR: Hydrocarbon Solvent | FLAME EXTENSION: 18" + |
| COLOR: White | SOLUBILITY IN WATER: 0% |
| DETERGENCY: None | SPECIFIC GRAVITY: 0.87 |
| TOXICITY: 400 ppm OSHA PEL | % VOLATILE BY VOLUME: 80.8% |
| WETTING ABILITY: None | pH: N/A |
| STORAGE STABILITY: 1 Year + | PROPELLANT: Hydrocarbon |
| COLD STABILITY: 0°F | EVAPORATION RATE: Medium |
| PHOSPHATES: None | BIODEGRADABILITY: None |
| VOC CONTENT: 53.9% | |

LABEL INFORMATION

WONDER ACOUSTICAL CEILING TILE RESTORER – WHITE

WONDER Acoustical Ceiling Tile Restorer is formulated to cover stains and smoke damage visible on acoustic ceiling tiles. Seals and covers water stains, smoke, graffiti, paint, ballpoint ink, permanent marker, and rusting nail heads. Permanently bonds to the surface without compromising sound absorption properties and fire retardant value.

WONDER works as a non-bleeding primer/sealer for sign painters, a non-grain raising primer for new wood, a base coat for wallpaper or vinyl wall coverings, and as a base coat for galvanized metal.

DIRECTIONS FOR USE Clean surface thoroughly to remove grease, dust, and other foreign matter. Shake can vigorously before and during use. From a distance of 12 inches, spray to coat surface lightly. Allow to dry, then follow with another light coat. Apply at temperatures above 65°F. One can covers 12–15 (2' x 4') tiles or 120 sq. ft.

NOTE: Following use, invert can and spray a short burst to clear nozzle for storage. If nozzle becomes clogged, remove and hold under running warm water.


DANGER: Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

MEETS CALIFORNIA VOC REACTIVITY LIMIT OF 1.20 FOR FLAT PAINT PRODUCTS.

CONTAINS (CAS#): Propane/n-Butane (68476-86-8), Petroleum Distillates, hydrotreated light (64742-47-8), Acetone (67-64-1), Titanium Dioxide (13463-67-7), Ethyl Alcohol (64-17-5), Heptane (142-82-5).

| | |
|--------------|---|
| HEALTH | 2 |
| FLAMMABILITY | 3 |
| REACTIVITY | 0 |
| PERSONAL | B |



PACKAGING INFORMATION

12 – 16 oz cans per case, 12 oz net weight