

CRUNCH

ORGANIC GEL ENGINE DEGREASER



DESCRIPTION

CRUNCH is a USDA authorized concentrated blend of organic solvents in a gel base. The gel base allows product to cling to vertical surfaces. It works quickly to penetrate and emulsify tar, asphalt, grease and oil. It washes off with water or solvent. This product is safe and easy to use. Spray on and wash off with water. Does not contain 1,1,1 Trichloroethane, CFC's or petroleum distillates.

APPLICATIONS

For use on tar, grease, oil, asphalt based roofing compounds, and asphalt based cements. Areas of use include automobile dealers, machine shops, industrial manufacturing, factories, fleet maintenance shops and marine equipment.

FEATURES & BENEFITS

- Gel-base—will not run—spray on—wash off
- Contains no chlorinated or fluorinated solvents
- Natural citrus solvent base—no offensive odor

SPECIFICATIONS

FORM: Solvent-Based Aerosol
ODOR: Citrus-petroleum
COLOR: Clear
DETERGENCY: Excellent
TOXICITY: 400 ppm OSHA TLV
WETTING ABILITY: Excellent
STORAGE STABILITY: 1 Year +
COLD STABILITY: 0°F
% VOC: 10%

FLASH POINT: N/A
FLAME EXTENSION: N/D
SOLUBILITY IN WATER: Moderate
SPECIFIC GRAVITY: 0.91-0.98
% VOLATILE BY VOLUME: 70%
pH: 10.8-12
PROPELLANT: Hydrocarbon
EVAPORATION RATE: Slow
BIODEGRADABILITY: Yes

LABEL INFORMATION

CRUNCH ORGANIC GEL ENGINE DEGREASER

A USDA authorized concentrated blend of organic solvents in a gel base. The gel base allows product to cling to vertical surfaces. It works quickly to penetrate and emulsify tar, asphalt, grease and oil. It washes off with water or solvent. This product is safe and easy to use. Spray on and wash off with water. Authorized for use in meat and poultry processing plants by the USDA. Does not contain chlorinated or fluorinated solvents.

DIRECTIONS FOR USE: When using on painted surfaces, test a small area to be sure paint is not affected. Hold can eight to ten inches from the surface to be sprayed. Apply a thorough coating, being sure to cover all grease, oil or tar.

FOR ENGINES: Cover carburetor intake and distributor with plastic or aluminum foil before using to avoid water contamination. Allow product to set for fifteen minutes to allow complete penetration and emulsification. Hose off with strong stream of water. Remove plastic or aluminium foil and run engine for fifteen minutes to insure complete drying.


OTHER SURFACES: To remove oil, grease, tar and asphalt from other surfaces, apply to surface covering area to be cleaned completely. Allow product to work for ten to fifteen minutes. Wash off with a strong stream of water. Heavily soiled areas may require scrubbing or a second application.

DANGER: Flammable Aerosol. Contains gas under pressure; May explode if heated. Causes skin irritation and serious eye damage. May be fatal if swallowed and enters airways. May cause an allergic skin reaction.

Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear eye/face protection and protective gloves. If on skin: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing must not be allowed out of the workplace. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Dispose of contents/container in accordance with local, state, and federal law.

CONTAINS (CAS#): Water (7732-18-5), Petroleum Distillates, hydrotreated light (64742-47-8), Nonoxynol (127087-87-0), Propane (74-98-6), Glycol Ether DPnB (29911-28-2).

HEALTH	1
FLAMMABILITY	2
REACTIVITY	0
PERSONAL	A



PACKAGING INFORMATION

12 – 20 oz. cans per case, 16 oz. net weight