

PRODUCT INFORMATION SHEET

ZENEX

INTERNATIONAL

One Zenex Circle • Cleveland, Ohio 44146
Toll Free: 866-217-5100 • Fax: 440-232-5101

Anti-Seize Copper

Premium Grade Anti-Seize & Lubricant
ZENEX NUMBER 494645

DESCRIPTION

This high temperature, anti-seizing agent can also be used as a quality protective coating. Temperature range to 2,000°F.

FEATURES AND BENEFITS

Provides excellent adhesion, high E.P. capability, water repellent, compatible with other lubricants, non-melting, non-gumming and non-hardening. Also prevents galling, seizing and galvanizing action. It is a premium coating for service in highly corrosive environments.

APPLICATIONS AND USES

For use on nuts, bolts, studs, etc. Acts as a lubricant on bearings and slides.

DIRECTIONS FOR USE

Spray only at temperatures above 60°F. Shake can vigorously for one minute after mixing ball begins to rattle. Make sure surface is cleaned of all dirt, grease and grime. Spray a liberal amount from 8 to 10 inches away. Invert can after use and spray short bursts to clear the valve.

SIZE / AVAILABILITY

16 oz. Aerosol
Net Weight 14 oz.
12 per case

STATE RESTRICTION

Not available for sale in California.



**Emergency
Phone Number
(800) 535-5053**

HMIS	
HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	B

