



## BLACK LABEL SERIES

## TFE DRY COATING LUBRICANT AND RELEASE AGENT

This non-oily, non-staining woodworker's lubricant remains dry during use. Extremely slick, T1 will not melt below 500°F, will not attract or hold dust or dirt and will not become gummy. Repels oil and water. Reduces friction. Inhibits resin build-up while it prolongs tool life.

- REPELS OIL & WATER
- FORTIFIED WITH TFE
- REDUCES FRICTION STOPS STICKING
- PROLONGS TOOL LIFE
- PAINTABLE WILL NOT AFFECT WOOD FINISH



 Dry coating lubricant for use on: saw blades, planers, router bits, drill bits, shapers, table tops. Use as a release agent for rubber, epoxy, phenolic, polyester and other resins.

WHMIS labeled for sale in Canada



Can Size: 20 oz.Net Weight: 12 oz.Shipping Weight: 14 lb.

Packaged: 12 cans per case
UPC Number: 0 41911 00295 0

Color: WhiteFragrance: Solvent

- Shelf Life: 1 Year +
- Ozone Depleting Compounds: None
- Recyclable Packaging: Yes
- VOC Compliant CARB/OTC: Yes
- Flammability: Extremely flammable
- 24 HOUR MEDICAL EMERGENCY: 1-866-836-8855



