



**SW464**  
**M<sup>2</sup>**

# BLACK LABEL SERIES

## DRY MOLY LUBRICANT

Temperature range - 110°F to 1050°F and pressures to 100,000 psi. Inert to water, oil alkalis and many acids. Will not attract dust. Excellent anti-seize properties on steel bolts in super heated steam installations after exposure to 1050°F and 20% salt solutions.

- ANTI-SEIZE
- ANTI-FRICTION FILM
- ANTI-CORROSION
- HIGH TEMPERATURE
- HIGH PRESSURE

### INDUSTRY USES:

Oil and Gas, Non Destructive Testing (NDT), Pipe Storage, Foundries, Automotive, Sewing Trades, Paper Converting, Chemical Plants, Textile Fibers, Woodworking.

Contains pure Molybdenum Disulfide for superior lubrication where oil is not desirable.

### DIRECTIONS:

Shake vigorously. Surface must be clean and dry prior to application. Spray from a distance of 8 to 10 inches. Apply a thin, uniform coating. Allow to set approximately 3 to 5 minutes before applying second coat. After each use, invert can, use a short spray to clear button.

WHMIS labeled for sale in Canada

### PRODUCT SPECIFICATIONS

- Can Size: 16 oz.
- Net Weight: 14 oz.
- Shipping Weight: 15 lbs.
- Packaged: 12 cans per case
- UPC Number: 0 41911 00464 0
- Color: Black
- Fragrance: Solvent
- Shelf Life: 1 Year +
- Ozone Depleting Compounds: None
- Recyclable Packaging: Yes
- VOC Compliant CARB/OTC: Yes
- Flammability: Extremely Flammable
- 24 HOUR MEDICAL EMERGENCY: 1-866-836-8855

NOTE: This product is EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.

