

Product Data Sheet

No. **35062** - 06/20

ANTI-VANDAL SPRAY

CARB VOC <50% (GRAFFITI REMOVER)

PRODUCT NUMBERS: 5062 - 13 OZ. NET. WT. AEROSOL

I. GENERAL DESCRIPTION

Description: This industrial strength Anti-Vandal Spray removes the most stubborn graffiti, such as spray paint, ink, crayon, lipstick and pencil from all hard surfaces.

Benefits: The use of this product eliminates the need to sandblast or grind marks off concrete and brick surfaces. Leaves no residue.

Applications: Use on road signs, washroom walls, trucks, sidewalks, public buildings, buses, bowling equipment, railroad bridges and underpasses. This product is harmless to all hard surfaces, tile, brick, aluminum, steel, brass, glass, chrome, vinyls, enamels, porcelain, marble, ceramics, Formica and more. Test for compatibility on synthetic surfaces, susceptible to solvent damage, such as rubber, asphalt tile, rubber base paints and plastics.

Directions: Spray on surface and wipe with clean cloth. If soil is stubborn repeat the application. In extreme cases, use bristle brush or nylon scrubbing pad and work into foreign material. Spray on and wipe again with clean cloth.

Limitations: Please refer to the Safety Data Sheet for specific information on material hazards, etc.

Packaging:

Aerosol:	Cans (16 oz.)	13 oz. net wt. (369 grams)	15.8 fl. oz. (467 ml)
	12 cans/case	14 lbs. (6.4 kg)	0.47 CF (0.013 CM)

II. CHARACTERISTICS & PROPERTIES

Specifications:

None

Appearance:

Non-foaming liquid

Color:

Colorless, transparent

Odor:

Ketone

Dry Schedule:

Not applicable

Performance and Chemical Properties:

Weight per gallon	6.9 lbs.
Specific gravity	0.82
Viscosity in centipoise	Not applicable
Flammability: Label marking	Extremely Flammable
Flash point.....	<1.4°F (-17°C)
Active ingredient by weight	96%
CARB VOC (graffiti remover)	<50%
Operating temperature range	40° to 110° F (4° to 43° C)
Boiling point @ 760mm Hg	N/A
Dielectric strength	TBD
Surface tension	TBD
Food contact rating	N/A

Base Materials

Solvents (top two)	Methyl Ethyl Ketone, Aliphatic Hydrocarbon
Propellant system.....	Carbon Dioxide

III. SHIPPING, STORAGE AND HEALTH

UN number	UN1950
Proper Shipping Description	Aerosols
Hazard Class	2.1
Packing Group	N/A
Limited Quantity	Yes
Warehouse storage level number	NFPA 30B Level 3
Storage temperature	32° to 120°F (0° to 49°C)
Shelf life	1 to 3 years
HMIS ratings	
Health	2
Fire	3
Reactivity	1

IV. MISCELLANEOUS

Contains no Ozone Depleting Substances (O.D.S.)

V. WARRANTY

1-year performance warranty on all products from date of purchase. Report to home office or local Aerovee representative for examination. Because Seller cannot control Buyer's handling or use of product, Seller makes no warranty expressed or implied when not used or stored in accordance with directions. Seller shall not be liable for cost of labor, incidental or consequential damages, and this warranty is limited to replacement of product or credit of purchase.